TH108PLUS

Baseboards & convectors

With TRIAC switching, this digital non-programmable model delivers exceptional accuracy and silent operation in a stylish, easy-to-use design with a backlit display

MODELS & RATINGS

TH108PLUS 3000 W @ 240 V 12.5 A resistive 60 Hz 2 wires / SPST

(Available only through authorized dealers)

(min. 2 A load)



SPECIFICATIONS

TEMPERATURE CONTROL
Microprocessor-optimized PIA
Heating cycles: 15 seconds

Accuracy: ± 0.15°C / 0.27°F

SWITCHING ACTION TRIAC: Silent operation

TEMPERATURE SETTING

Manual

°C or °F selectable

DIMENSIONS (H•W•D)

120 x 115 x 26 mm / 4.8 x 4.5 x 1 inches

FEATURES

Ultimate temperature control – the most accurate type of thermostat on the market (± 0.15°C / 0.27°F)

On-screen heating power indicator gives at-a-glance verification of power being used

2-wire non-polarized connection means fast, hassle-free installation


Up/down buttons enable easy temp. setting

Also ideal for radiant ceilings

Backlit display for easy reading

Battery free

INSTALLATION



 $T_A = Ambient Temperature$





The advantages of TRIAC switching

Although the TH108PLUS is non-programmable, its TRIAC precision still saves up to 10% on your heating bill. Here's how:

- Unsurpassed precision eliminates temperature swings
- No temperature swings means you are comfortable at a lower setpoint
- · Comfort at a lower setpoint saves money on heating bills